

Product	Model No.	K220	
Display	LCD	Size	21.5inch 16:9 LCD Panel
		Back light	LED Backlight, 30,000hrs
		Brightness	250nits
		Resolution	1920x1080
	Touch Screen	Touch Solution	Project Capacitive Touch Screen
System	CPU	Intel i5-3550S 3.7GHz LGA1155/6M CACHE	
	Memory	4GB DDR3-1600 SO-DIMM	
	HDD	250GB SATA HDD, 7200RPM	
	Power Supply	220W FlexATX Power Supply	
	Thermal Printer	3" Receipt Printer w/paper near end sensor, 180mm/s	
	Speaker	2 x 2W speaker	
I/O	VGA	1	
	HDMI	1	
	Ethernet	2 x RJ45	
	USB	4 x USB3.0 / 2 x USB2.0	
	Serial port	2 (RS232/422/485)	
	Audio	Line out / MIC	
Operation System	OS	Option: Windows 7 Embedded Standard Windows 7 Professional Windows 8.1 Professional Windows 8.1 Industry Pro Windows 10 IOT Professional	
Power Voltage		100~240 VAC	
Power Frequency		50Hz~60Hz (The spec of AC Adaptor: 47Hz-63Hz)	
Temperature	Operating Temperature: 0~40°C Humidity: 20~80%		
	Storage Temperature: -20~80°C		